# Domus Ergo-line Flex

**18251** The central idea behind the Domus relax chair is to offer optimal seating comfort in peace and quiet.

The <u>Ergo-line</u> mechanism makes sure that the backrest, seat and legrest simultaneously tilt into a "zero gravity" position.

# Support

- The rounded sides consist of 2 OSB boards of 30 mm, and are firmly connected with a metal structure.
- The sides are upholstered with fire-retardant foam.
- The upholstery is finished with imitation leather and decorative stitching.
- Comfortable rounded armrests of  $\pm$  5 cm.
- Dinner tray attachment.
- All edges and corners have been rounded.
- No visible fastening elements.
- Design castors Ø 65 mm with brake.
- Optionally possible on solid beech legs, with aid castors at the back.

#### Seat

- Removable seat in melaminated MDF, thickness: 12 mm.
- The rounded seat in front stimulates a fluent blood circulation.
- Comfortable seat height of 45 cm.
- Upholstered with fire-retardant foam. Two different density zones guarantee optimal seating comfort.
- The upholstery is finished with imitation leather and decorative stitching.

## **Backrest and legrest**

- The backrest consists of an ergononomic pre-shaped plywood shell, thickness 12 mm.
- Upholstered with fire-retardant foam. This foam has 3 different density zones to guarantee optimal seating comfort.
- The upholstery is finished with imitation leather and decorative stitching.
- Equipped with an adjustable and removable head/neck cushion.

#### Ergo-line mechanism:

- Makes sure that the backrest, seat and legrest simultaneously tilt into a zero gravity position (\*) by means of a lever that is situated on the right inside of the chair.
- The angle between the seat and backrest ranges from 97° (seating position) to 120° ('zero gravity' position).
- When the relax mechanism is activated, the seat inclines to a 24 degree angle.
- A gas spring minimizes the necessary activation strength of the mechanism.
- Thanks to a lever that is situated on the right inside of the chair, it is possible to lock the chair in every position.
- When the chair is put in the seat position, the legrest will be turned inwards so that you can stand up without any problem.

#### Colours


We would like to refer to our extensive colour gamut. Sample card + samples available on request.

(\*) Zero gravity position: this seat/lying position is based on NASA data. A neutral body position converts all muscle power into a biomedical balance. (Source: "From outer space to you", Omni, March 1994.)



#### 18251 | Domus Ergo-line Flex:

- L 62 x D 73 x H 115 cm
- Seat height: 44 cm
- Seat depth: 51 cm
- Seat width: 52 cm
- Height armrests: 64 cm
- Safe working load: 135 kg



## Materials and finishing

- Wood: Solid beech, Plywood, OSB, MDF.
- Metal: epoxy coating (light grey).
- Fire-retardant foam.
- <u>Upholstery</u>: see collection.
- Resistant to the common cleaning products.

For further information about used materials, constructions and maintenance: consult our materialfiles.

## **Options**

- Wooden / synthetic armrests.
- Abduction block combined with the dinner tray.
- Cushion with visco-elastic foam and a bi-elastic cover.
- Anatomical reduction cushion.
- Lateral headrest.
- Bracket for fixation straps.
- Armrests with removable upholstery.
- Case for IV rod and/or IV rod.
- Wooden legs and aid castors at the back.
- Hook for dinner tray.
- Design castors ø 100 mm with brake.
- Design castors ø 100 mm with brake and 2 directional castors.
- Footrest (only with castors ø 100 mm).
- Removable headrest.

